

SPT1009 loading chart of outriggers at the max. position(other position)- 6 fall

working radius (m)	loading chart (t)									
	6.00 boom		9.40 boom		12.80 boom		16.20 boom		19.60 boom	
	other	Max.	other	Max.	other	Max.	other	Max.	other	Max.
2.50	10.00	10.00	8.50	8.50	5.50	5.50	4.00	4.00	—	—
3.00	9.20	9.20	7.50	8.50	5.50	5.50	4.00	4.00	3.00	3.00
3.50	8.00	8.00	6.50	7.50	4.80	5.50	3.60	4.00	3.00	3.00
4.00	6.80	6.80	5.50	6.40	4.70	5.50	3.50	4.00	3.00	3.00
4.50	5.60	6.00	4.80	5.60	4.70	5.20	3.45	4.00	3.00	3.00
5.00	4.80	5.20	4.00	4.80	4.00	4.80	3.20	4.00	3.00	3.00
5.40	3.80	4.70	3.10	4.60	3.10	4.50	3.10	3.80	3.00	3.00
6.00			3.00	3.80	3.00	3.60	3.00	3.40	3.00	3.00
7.00			2.00	3.00	2.00	3.00	2.00	3.00	2.00	2.80
8.00			1.80	2.60	1.80	2.60	1.80	2.60	1.80	2.60
8.80			1.60	2.30	1.60	2.30	1.60	2.30	1.60	2.30
9.50					1.40	2.20	1.40	2.20	1.40	2.20
10.00					1.20	2.00	1.20	2.00	1.20	2.00
11.00					0.80	1.70	0.80	1.70	0.80	1.70
12.20					0.70	1.40	0.70	1.40	0.70	1.40
13.00							0.65	1.20	0.65	1.20
14.00							0.60	1.10	0.60	1.10
15.00							0.50	1.00	0.50	1.00
15.60							0.40	0.85	0.40	0.85
16.00									0.40	0.80
17.00									0.35	0.75
18.00									0.30	0.65
19.00									0.20	0.50

SPT1009 loading chart of outriggers at the max. position(other position)- 4 fall

working radius (m)	loading chart (t)									
	6.00 boom		9.40 boom		12.80 boom		16.20 boom		19.60 boom	
	other	Max.	other	Max.	other	Max.	other	Max.	other	Max.
2.50	6.60	6.60	6.60	6.60	5.50	5.50	4.00	4.00	—	—
3.00	6.60	6.60	6.60	6.60	5.50	5.50	4.00	4.00	3.00	3.00
3.50	6.60	6.60	6.50	6.60	4.80	5.50	3.60	4.00	3.00	3.00
4.00	6.60	6.60	5.50	6.40	4.70	5.50	3.50	4.00	3.00	3.00
4.50	5.60	6.00	4.80	5.60	4.70	5.20	3.45	4.00	3.00	3.00
5.00	4.80	5.20	4.00	4.80	4.00	4.80	3.20	4.00	3.00	3.00
5.40	3.80	4.70	3.10	4.60	3.10	4.50	3.10	3.80	3.00	3.00
6.00			3.00	3.80	3.00	3.60	3.00	3.40	3.00	3.00
7.00			2.00	3.00	2.00	3.00	2.00	3.00	2.00	2.80
8.00			1.80	2.60	1.80	2.60	1.80	2.60	1.80	2.60
8.80			1.60	2.30	1.60	2.30	1.60	2.30	1.60	2.30
9.50					1.40	2.20	1.40	2.20	1.40	2.20
10.00					1.20	2.00	1.20	2.00	1.20	2.00
11.00					0.80	1.70	0.80	1.70	0.80	1.70
12.20					0.70	1.40	0.70	1.40	0.70	1.40
13.00							0.65	1.20	0.65	1.20
14.00							0.60	1.10	0.60	1.10
15.00							0.50	1.00	0.50	1.00
15.60							0.40	0.85	0.40	0.85
16.00									0.40	0.80
17.00									0.35	0.75
18.00									0.30	0.65
19.00									0.20	0.50

SPT1009 loading chart of outriggers at the max. position(other position)- 2 fall

working radius (m)	loading chart (t)									
	6.00 boom		9.40 boom		12.80 boom		16.20 boom		19.60 boom	
	other	Max.	other	Max.	other	Max	other	Max	other	Max
2.50	3.30	3.30	3.30	3.30	3.30	3.30	3.30	3.30	—	—
3.00	3.30	3.30	3.30	3.30	3.30	3.30	3.30	3.30	3.00	3.00
3.50	3.30	3.30	3.30	3.30	3.30	3.30	3.30	3.30	3.00	3.00
4.00	3.30	3.30	3.30	3.30	3.30	3.30	3.30	3.30	3.00	3.00
4.50	3.30	3.30	3.30	3.30	3.30	3.30	3.30	3.30	3.00	3.00
5.00	3.30	3.30	3.30	3.30	3.30	3.30	3.20	3.30	3.00	3.00
5.40	3.30	3.30	3.10	3.30	3.10	3.30	3.10	3.30	3.00	3.00
6.00			3.00	3.30	3.00	3.30	3.00	3.30	3.00	3.00
7.00			2.00	3.00	2.00	3.00	2.00	3.00	2.00	2.80
8.00			1.80	2.60	1.80	2.60	1.80	2.60	1.80	2.60
8.80			1.60	2.30	1.60	2.30	1.60	2.30	1.60	2.30
9.50					1.40	2.20	1.40	2.20	1.40	2.20
10.00					1.20	2.00	1.20	2.00	1.20	2.00
11.00					0.80	1.70	0.80	1.70	0.80	1.70
12.20					0.70	1.40	0.70	1.40	0.70	1.40
13.00							0.65	1.20	0.65	1.20
14.00							0.60	1.10	0.60	1.10
15.00							0.50	1.00	0.50	1.00
15.60							0.40	0.85	0.40	0.85
16.00									0.40	0.80
17.00									0.35	0.75
18.00									0.30	0.65
19.00									0.20	0.50

SPT1009 loading chart of outriggers at the max. position(other position)- 1 fall

working radius (m)	loading chart (t)									
	6.00 boom		9.40 boom		12.80 boom		16.20 boom		19.60 boom	
	other	Max.	other	Max.	other	Max.	other	Max.	other	Max.
2.50	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	—	—
3.00	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
3.50	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
4.00	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
4.50	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
5.00	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
5.40	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
6.00			1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
7.00			1.60	1.60	1.60	1.60	1.60	1.60	1.60	2.80
8.00			1.60	1.60	1.60	1.60	1.60	1.60	1.60	2.60
8.80			1.60	1.60	1.60	1.60	1.60	1.60	1.60	2.30
9.50					1.40	1.60	1.40	1.60	1.40	2.20
10.00					1.20	1.60	1.20	1.60	1.20	2.00
11.00					0.80	1.60	0.80	1.60	0.80	1.70
12.20					0.70	1.40	0.70	1.40	0.70	1.40
13.00							0.65	1.20	0.65	1.20
14.00							0.60	1.10	0.60	1.10
15.00							0.50	1.00	0.50	1.00
15.60							0.40	0.85	0.40	0.85
16.00									0.40	0.80
17.00									0.35	0.75
18.00									0.30	0.65
19.00									0.20	0.50

SPT1009 loading chart of outriggers at the max. position(other position)- Search hook

working radius (m)	loading chart (t)									
	6.00 boom		9.40 boom		12.80 boom		16.20 boom		19.60 boom	
	other	Max.	other	Max.	other	Max.	other	Max.	other	Max.
2.50	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	—	—
3.00	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
3.50	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
4.00	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
4.50	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
5.00	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
5.40	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
6.00			1.60	1.60	1.60	1.60	1.60	1.60	1.60	3.00
7.00			1.60	1.60	1.60	1.60	1.60	1.60	1.60	2.80
8.00			1.60	1.60	1.60	1.60	1.60	1.60	1.60	2.60
8.80			1.60	1.60	1.60	1.60	1.60	1.60	1.60	2.30
9.50					1.40	1.60	1.40	1.60	1.40	2.20
10.00					1.20	1.60	1.20	1.60	1.20	2.00
11.00					0.80	1.60	0.80	1.60	0.80	1.70
12.20					0.70	1.40	0.70	1.40	0.70	1.40
13.00							0.65	1.20	0.65	1.20
14.00							0.60	1.10	0.60	1.10
15.00							0.50	1.00	0.50	1.00
15.60							0.40	0.85	0.40	0.85
16.00									0.40	0.80
17.00									0.35	0.75
18.00									0.30	0.65
19.00									0.20	0.50